

GENERAL SPECIFICATIONS

Refrigerant: R410a
Maximum Wall Thickness: 13-13/16"
Warranty: 2 Year Full/5 Year Sealed System
Shipping Weight (lbs): 126
Product Weight (lbs): 102
Power Type: None
Size: N/A
Installation Type: Built-In
Collection: Frigidaire

CERTIFICATIONS & APPROVALS

Safety Certification: UL/CUL/CSA

AC SPECIFICATIONS

Air Intake: Fresh or Recycled Air
Air Direction Control: Auxiliary 2-Way
Air Volume (CFM) (Max./Med./Min.):
302/284/267
Charge (ozs): 24.70
Slide-Out Chassis: Yes
Energy Saver: Yes
Auto Fan: Yes
Filter Access: Slide-Out
Filter Type: PA/Nylon Mesh
Fin Coating: Normal
Low Voltage Start-Up: Yes
Motor RPM (High/Med/Low): 1030/970/890
Noise Level dB (High/Med/Low): 51/50/49
Quiet Start-Up: Yes
Random Restart Protection: Yes
Room Freeze Protection: Yes

ELECTRICAL SPECIFICATIONS

Amps (Electrical Heat): 13.2 / 12.2
Amps (Heat Pump): 2.4 / 2.5
Amps (Cool): 2.8 / 3.0
Circuit Breaker: 20A
Cable Included: Yes
Horsepower (Cool): 0.85
Voltage Rating: 230V / 208V, 60Hz
Watts (Cool): 640 / 620
Watts (Electrical Heat): 3,000 / 2,452
Watts (Heat Pump): 540 / 530

PERFORMANCE

Performance Certification: AHRI & CEC
BTU (Cool): 7,700 / 7,600
Cool Area (Sq. Ft.): 320
Dehumidification (Pints/Hour): 17
Energy Efficiency Ratio: 12.0 / 12.2
BTU (Electrical Heat): 10,200 / 8,300
BTU (Heat Pump): 6,300 / 6,100

EXTERIOR DIMENSIONS

Height: 16"
Width: 42"
Depth: 13-13/16"

CONTROLS

Control Location: Top Right