




Full Range of Model Specifications.

Kühl comes in a range of sizes and capacities. Click on the model number for detailed installation information. Take a look.

We've also included definitions of some common air conditioning terms. [Contact us](#) if you would like us to add one that we've missed.

Cooling Capacity		5200–36000 Btu/hr
Heating Capacity		4000–22000 Btu/hr
EER		8.5–11.5

Moisture Removal		.5–12.0 pints/hr
Air Circulation (CFM)		190–725 ft ³ /min

Kühl

Model	Cooling Capacity (Btu/hr)	Heating Capacity (Btu/hr)	EER	Energy Star Qualified	Min. Extension Into Room	Min. Extension Outside
▶ SQ05N10B	5200	n/a	11.2	Yes	5 1/2"	10 3/4"
▶ SQ06N10B	5700	n/a	11.2	Yes	5 1/2"	10 3/4"
▶ SS08N10B	8000	n/a	11.2	Yes	5 3/4"	16 15/16"
▶ SQ08N10B	7900	n/a	11.5	Yes	5 1/2"	10 3/4"
▶ SS10N10B	9700	n/a	11.3		5 3/4"	16 15/16"
▶ SQ10N10	9600	n/a	9.8		5 1/2"	10 3/4"
▶ SS12N30B	12000/12000	n/a	11.3/11.3	Yes	5 3/4"	16 15/16"
▶ SS12N10B	12000	n/a	11.3	Yes	5 3/4"	16 15/16"
▶ SS14N10A	13500	n/a	10.8		5 3/4"	16 15/16"
▶ SM15N10B	15000	n/a	11.2	Yes	5 3/4"	16 15/16"
▶ SS16N30	15500/15200	n/a	10.7/10.7		5 3/4"	16 15/16"
▶ SM18N30	17500/17200	n/a	10.7/10.7		5 3/4"	16 15/16"
▶ SM21N30B	20500/20000	n/a	9.8/9.7	Yes	5 3/4"	16 15/16"
▶ SM24N30A	23500/23200	n/a	8.5/8.5		5 3/4"	18 15/16"
▶ SL24N30B	24000/23800	n/a	9.8/9.8	Yes	5 3/8"	18 15/16"
▶ SL28N30B	28000/27600	n/a	9.8/9.6	Yes	5 3/8"	18 15/16"
▶ SL36N30B	36000/35500	n/a	9.0/9.0		5 3/8"	18 15/16"





Kühl+ Heat Pump

Model	Cooling Capacity (Btu/hr)	Heating Capacity (Btu/hr)	EER	Energy Star Qualified	Min. Extension Into Room	Min. Extension Outside
▶ YS10N10B	9500	8000	10.4	Yes	5 3/4"	16 15/16"
▶ YS12N33B	11500/11300	9400/9000	10.4/10.4	Yes	5 3/4"	16 15/16"
▶ YM18N34B	17500/17200	15500/15400	10.4/10.4	Yes	5 3/4"	16 15/16"
▶ YL24N35B	24000/24000	22000/22000	9.8/9.8	Yes	5 3/8"	18 15/16"

Kühl+ Electric Heat

Model	Cooling Capacity (Btu/hr)	Heating Capacity (Btu/hr)	EER	Energy Star Qualified	Min. Extension Into Room	Min. Extension Outside
▶ EQ08N11B	7500	4000	11.0		5 1/2"	10 3/4"
▶ ES12N33B	12000/12000	10700/8900	11.3/11.3		5 3/4"	16 15/16"
▶ ES16N33	15500/15200	10700/8900	10.7/10.7		5 3/4"	16 15/16"
▶ EM18N34	17500/17200	13000/10600	10.7/10.7		5 3/4"	16 15/16"
▶ EM24N34A	23500/23200	13000/10600	8.5/8.5		5 3/4"	16 15/16"
▶ EL36N35B	36000/35500	17300/14300	9.0/9.0		5 3/8"	18 15/16"

Electrical Outlet Information

 <p>Rating: 125V — 15A Models: SQ05N10B, SQ06N10B, EQ08N11B, SS08N10B, SQ08N10B, SS10N10B, YS10N10B, SQ10N10, SS12N10B, SS14N10A, SM15N10B</p>	 <p>Rating: 250V — 15A Models: SS12N30B, SS16N30, SM18N30, SM21N30B</p>	 <p>Rating: 250V — 20A Models: ES12N33B, YS12N33B, ES16N33, SM24N30A, SL24N30B, SL28N30B</p>	 <p>Rating: 250V — 30A Models: EM18N34, YM18N34B, YL24N35B, EM24N34A, SL36N30B, EL36N35B</p>
--	---	--	--